

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 891.7270
MSDS NUMBER: 891.7270.7
IDENTITY: LONG HAUL CHAIN & CABLE LUBE Revision Date: 02/22/2010

=====

Section I

=====



Manufactured For:
Winzer Corporation
10560 Markison Rd
Dallas, Texas 75238
800-527-4126

INFOTRAC EMERGENCY
PHONE #: (800) 535 5053

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
HYDROTREATED NAPTH. DIST *	64742-52-5	5 MG/M3	5 MG/M3	N/A	_____
PROPANE/N-BUTANE	68476-86-8	N/A	1000ppm	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	500+	Specific Gravity (water=1)	0.91
Vapor Pressure (mm Hg)	.01	Melting Point:	N/A
Vapor Density (AIR=1)	>1	Evaporation Rate:	N/A
Solubility in Water:	0%	(Butyl Acetate=1)	
Appearance and Odor:	GRAY-BLACK LIQUID, MILD SOLVENT ODOR		

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point (Method Used): +200F TCC Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: CO2, FOAM, WATER, DRY CHEMICAL
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. FLAMMABLE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 5891.7270

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F
Incompatibility (Materials to Avoid): NONE

Hazardous Decomposition or Byproducts: OXIDES OF CARBON

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS. INGESTION: NAUSEA, SICKNESS. EYES: IRRITATION.
SKIN: MAY CAUSE LOCALIZED DRYNESS.

Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INGESTION: DO NOT INDUCE VOMITING-
CONTACT PHYSICIAN IMMEDIATELY. EYES: FLUSH WITH WATER FOR 15 MINUTES.
CONSULT PHYSICIAN IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR.
CONSULT PHYSICIAN IF NEEDED. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: CLEAN UP WITH
RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL GUIDELINES. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT PUNCTURE OR
INCINERATE CONTAINER. DO NOT REUSE CONTAINER.

Other Precautions: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREA.
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED,
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USE.